

Residential Aluminum Fencing Specifications Chart

PANELS

Material: 6063-T3 aluminum Rails: 1" x 1" x 0.055" thick

Pickets: 0.59" x 0.59" x 0.05" thick

Picket Spacing: 3-13/16" (1-5/8" on Chatham style and 1-5/16" on Cheshire style)

Available Heights: 48", 52", 54", 60" and 72" depending on style

Available Colors: Black, White and Bronze AAMA 2604 Polyester Powder Coating

Warranty: Limited Lifetime

Screws: Rust resistant colored head; some styles available as screw-less

All panels are pre-assembled

Standard Packaging: 10 panels per carton

Posts:

Material: 6063-T3 aluminum

Line/Corner Posts: 2" square x 0.062" thick

End/Gate Posts: 2" square x 0.080" thick (0.125" thick also available)

Available Heights: 72", 79", 84" and 96" depending on style

Available Colors: Black, White and Bronze AAMA 2604 Polyester Powder Coating

Warranty: Limited Lifetime

All posts are pre-punched to accept panel rolls Standard Packaging: 6 or 12 posts per carton

Post Spacing: 72-1/2" on center

Gates:

Material: 6063-T3 aluminum

Frame: 0.118" thick

Rails: 1" x 1" x 0.055" thick

Pickets: 0.059" x 0.059" x 0.05" thick Welded frame and picket construction

Available Heights: 48", 52", 54", 60" and 72" depending on style

Available Widths: 4', 5', 6' and 8' depending on style

Available Styles: Straight Top, Arched Top and Rainbow Arch Styles

Available Colors: Black, White and Bronze AAMA 2604 Polyester Powder Coating

Warranty: Limited Lifetime